




Unichrome Air Bath Shower Mixer

thermostatic mixer shower

mixer showers



Dimensions given are approximate

| | |
|---------------------------------------|---|
| Temperature Control | Thermostatic |
| Plumbing System Compatibility | High pressure or low pressure with a pump |
| Inlet Connections | 3/4" BSP |
| Water Entry Points | Rising |
| Outlet Connection | 1/2" BSP bottom |
| Minimum Running Pressure/Flow | 1 Bar @ 8l/min or 0.1 Bar (with a pump) |
| Maximum Running Pressure | 5 Bar |
| Maximum Static Pressure | 10 Bar |
| Open Outlet Flowrate at 1 Bar | 13l/min |
| Maximum Flow with Flow Limiter Fitted | 8l/min |
| Pipe Inlet Centres | 176mm |
| Approvals, Complies with | BS-En 1111, 1287 |
| Guarantee | 5 years |

Operating Features

- Thermostatic to within 2°C
- Automatic shutdown if hot or cold supplies fail
- Adjustable maximum temperature stop
- Numbered temperature control
- Separate flow and temperature controls
- Supplied with either a shower kit (UNAITHBSMRR) or with a fixed showerhead holder (UNAITHBSM)
- Flow limiter supplied
- Rub clean showerhead – 5 spray pattern

| Finish | Code |
|--------|-------------|
| Chrome | UNAITHBSM |
| Chrome | UNAITHBSMRR |